



## Analytical Balance TRAB-605

[www.safezex.com](http://www.safezex.com) | [info@safezex.com](mailto:info@safezex.com)

## **Description**

Analytical Balance TRAB-605 is a fully automatic, internal calibration device with a completely transparent glass windshield. It has a huge backlit LCD, which improves the operator's visibility. It can weigh up to 410 g from 0 and has a minimum reading of 0.001 g. It is a faster and much more reliable device.

## **Features:**

It has humanized design, novel structure, and 5 fully transparent glass windshield surfaces

With the piece, unit conversion, full-range peel, zero tracking, and other features such as multi-functionality, simple and dependable operation

Includes an RS232C output interface that can be directly connected to a computer, printer, another device

It employs a double CAM experiment with a fully automatic internal calibration function, which increases its stability and speed

The Balance includes applications such as preheating, calibration, screen saver, and others

The large backlit LCD screen improves the operator's vision by making it more soft and clear

## Specifications :

<b>Linear Error</b>	±0.002 g
<b>Minimum Reading</b>	0.001g
<b>Output Interface</b>	Rs232C
<b>Pan Size</b>	90 mm
<b>Power</b>	220V+22V/-33V, 50Hz
<b>Repeatability Error</b>	0.001 g
<b>Scale Interval</b>	1 mg
<b>Size</b>	330×215×350 mm
<b>Weighing Range</b>	0 to 410 g
<b>Weight</b>	5.5 Kg



W 84th Terrace Lenexa KS 66214, USA  
Email: [info@safezex.com](mailto:info@safezex.com) | Website: [www.safezex.com](http://www.safezex.com)