



Flame Photometer TRFP-603

www.safezex.com | info@safezex.com

Description

Flame Photometer TRFP-603 is equipped with a 7-inch LCD touch screen and having with a programmed calculation of the correlation coefficient. It has the ability of simultaneous measurement of the elements Na, K, Ca, Ba, and Li. It is a flameout protection device and comes with an air compressor. It has a compassion range of elements. In addition, the repeatability of elements is 1% CV for 20 consecutive samples and can accept the sample 6L/min.

Features:

It has a 7-inch LCD touch-screen

Consistent, simultaneous measurement of elements

It can automatically calculate the coefficient correlation

Flameout protection device

LPG is a flammable gas

Information of direct concentration

Flame size pre-selection

Range shifts were quantified

The device contains an air compressor

Specifications :

Gross Weight	17 kg
Linearity	0.195ppm?0.39 to 3.12?ppm, 0.69ppm?1.15 to 9.2?ppm, 0.15ppm?0.25 to 5?ppm
Package	570×530×380mm 0.115M3
Range	0 to 100 ppm
Repeatability	1 % CV for 20 consecutive samples
Respond time	8s
Sample uptake	6L/min
Sensitivity	0.1ppm



W 84th Terrace Lenexa KS 66214, USA
Email: info@safezex.com | Website: www.safezex.com