



Tilting Shaker TRTS-602

www.safezex.com | info@safezex.com

Description

Tilting Shaker TRTS-602 has a dual LCD screen that shows time and speeds separately. It has a working temperature range of 5 to 40 °C and a DC motor control system that controls the mechanism. It has a 10 ° inclination and a speed range of 10 to 70 revolutions per minute. A constant or countdown procedure is presented from 1 minute to 19h 59min. Various inserts and fixings are included, as well as a data access mode of RS232. It has a 10-degree inclination and a speed range of 10 to 70 revolutions per minute.

Features:

It has a dual LCD screen, an LCD screen that displays time and speeds separately

The mechanism that is controlled by a DC motor control system

Provided with various inserts and fixings

Having a constant or countdown procedure mode

Specifications :

Angle of Inclination	10°
Data Access	RS232
Dimension (L×W×H)	425×355×180mm
Maximum Load	10 kg
Moisture	0.8
Motor Type	DC motor
Operation Model	Time set, continuous operation
Power	40W
Speed Indicator	LCD
Speed Range	10 to 70rpm
Time Range	1 min to 19h59min
Timer Indicator	LCD
Voltage	100 to 240V, 50/60Hz
Weight	9kg
Working Temperature	5 to 40°,



W 84th Terrace Lenexa KS 66214, USA
Email: info@safex.com | Website: www.safex.com