



Ultrasonic Cleaner TRUC-607

www.safezex.com | info@safezex.com

Description

Ultrasonic Cleaner TRUC-607 has an ultrasonic vibration frequency of interaction composed of high-quality SUS304 stainless steel stampings. It has a 30 L capacity, a heating temperature range of 20 to 80°C, and a digital timer with a setting range of 0 to 99 minutes. It does not have a drainage ball valve.

Features:

The intensity of ultrasonic vibration, thoroughly solve the ultrasonic cleaning

Its work-performed tank is made of high-quality SUS304 stainless steel molding

The bladder is made of high-quality steel material, and the cladding is made of aluminum

Electronic timer with a period range of 0 to 99 minutes

The drainage ball valves are installed in drainage systems 6L and higher models

Specifications :

1 Unit Packing	66×44×48 cm
1 Unit Weight	15 Kg
Dimensions	55×33×36 Cm
Drainage	With
Heating Power	800W
Heating Temperature	20 To 80°
Overall Packing	67×46×89 Cm
Rinse Tank Size	50×30×20 cm
Timer	0 To 99min
Ultrasonic Frequency	28/40khz
Ultrasonic Power	600W
Volume	30 L
Weight	32 Kg



W 84th Terrace Lenexa KS 66214, USA
Email: info@safex.com | Website: www.safex.com